

US009408771B2

(12) United States Patent

Branch et al.

(10) Patent No.: US 9,408,771 B2

(45) **Date of Patent:** Aug. 9, 2016

(54) BLADDER DRIVEN LINEAR CYLINDER AND ASSOCIATED DEVICES DRIVEN THEREBY

(75) Inventors: **Thomas P. Branch**, Atlanta, GA (US);

Thomas Cunningham, Atlanta, GA (US); Edward Dittmar, Marietta, GA (US); Cale Jacobs, Suanee, GA (US)

(73) Assignee: **ERMI, INC.**, Atlanta, GA (US)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 923 days.

(21) Appl. No.: 13/220,348

(22) Filed: Aug. 29, 2011

(65) **Prior Publication Data**

US 2012/0053495 A1 Mar. 1, 2012

Related U.S. Application Data

- (60) Provisional application No. 61/377,688, filed on Aug. 27, 2010, provisional application No. 61/385,792, filed on Sep. 23, 2010.
- (51) Int. Cl.

A61H 1/02 (2006.01) *A61F 5/042* (2006.01)

(52) U.S. Cl.

(Continued)

(58) Field of Classification Search

CPC A61H 1/02; A61H 1/0218; A61H 1/0174; A61H 1/0285; A61H 1/0288; A61H 2201/1638; A61H 2201/0103; A61H 2201/123; A61H 2201/1246; A61H 2201/1481; A61H 1/0274; A61F 5/042 USPC 601/5, 9, 23, 24, 26, 27, 33, 34, 35, 40, 601/55, 61, 75, 84, 86, 88, 90, 96, 98, 105,

601/148–152; 602/13 See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

T100,602 I4 5/1981 Roley et al. 4,294,141 A 10/1981 Miller 4,407,277 A 10/1983 Ellison 5/1986 Petrofsky (Continued)

FOREIGN PATENT DOCUMENTS

CA 2615171 1/2007 DE 36 09 535 9/1987 (Continued)

OTHER PUBLICATIONS

B.D. Beynnon et al., "The Effect of Functional Knee-Braces On Strain On The Anterior Cruciate Ligament In Vivo," Journal of Bone and Joint Surgery; Boston, US; vol. 74A, No. 9; Oct. 1, 1992; pp. 1298-1312; XP000322579.

(Continued)

Primary Examiner — Quang D Thanh (74) Attorney, Agent, or Firm — Moore & Van Allen, PLLC; Patrick B. Horne

(57) ABSTRACT

An apparatus for manipulating the joint of a patient is provided. The apparatus comprises an actuator and a linkage. The actuator itself comprises: 1) a cylinder portion defining an interior cavity; and 2) an inflatable bladder member at least partially inside the cavity of the cylinder portion. The linkage is operatively positioned intermediate the actuator and the joint of the patient, the linkage configured to be activated and to flex the joint upon inflation of the bladder. A piston portion may also be provided and configured to move relative to cylinder portion within the cavity in response to inflation of the bladder. A patient connection and manipulation device may also be provided within the apparatus and configured to be attached relative to the patient, attached intermediate the linkage and the patient, and configured to at least partially assist with treatment upon activation of the linkage.

33 Claims, 30 Drawing Sheets

